

## So-PowerPointPP-VIP4-0,6t-M12 with variable length

Artikel-Nr:

8600320



Thread reach from  $F = 12-140 \text{ mm}$  is available. (with through thread)

When ordering implicitly indicate the required length.

Connection only with RUD approved components e.g; VCÖH-4, oval link, PP 0,6t kg or the 4 mm VIP chain.


Hint : The VIP chain connection is fool proof. When assembling the components, pay attention to the correct WLL allocation.

- **Can be combined with most commercial lifting means without additional connecting element.**
- **Lifting points pivots  $360^\circ$ .**
- **Large distance between bolt-on surface and load to avoid damage.**
- **Rotatable at nominal WLL,  $90^\circ$  to the bolt-on direction**Lowest kinking possibility due to cardan joint.
- Clear marking of the minimum WLL for all loading directions.
- Variable thread lengths are available for use of threaded holes and through hole fixtures.
- Non removable special bolt (this reduces the risk of non standard bolts).
- Component according to the test criterias of BG/DGUV "GS-OA-15-04".
- Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.
- Please observe torque instructions when lifting point is permanently installed resp. at constant swivelling operations and tilting/ turning actions.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

So-PowerPointPP-VIP4-0,6t-M12 with variable length

Artikel-Nr: 8600320



Nominal WLL	600 kg	1320 lbs
T	47 mm	1-7/8"
A	4 mm	5/32"
D	42 mm	1-21/32"
E	36 mm	1-27/64"
F	12-140 mm	12-140
M	M12 mm	M12