

So-PowerPoint PP-VIP10-3,5t-1"-8UNC with variable length

Artikel-Nr:

8600323




From the factory, bolt lengths from F=25-74 can be supplied (with an approximately 31 mm shank without thread). When ordering implicitly indicate the required length. WLL is equivalent to that of VWBG-V, since a corresponding lower part is used. Connection only with RUD approved components e.g; VCÖH-10, oval link, PP 3,5tkg or the 10 mm VIP chain. Hint : The VIP chain connection is fool proof. When assembling the components, pay attention to the correct WLL allocation.

- **Can be combined with most commerical lifting means without additional connecting element.**
- **Lifting points pivots 360°.**
- **Large distance between bolt-on surface and load to avoid damage.**
- **Rotatable at nominal WLL, 90° to the bolt-on direction**Lowest kinking possibility due to cardan joint.
- **Suspension ring with enlarged pivoting area.**
- Clear marking of the minimum WLL for all loading directions.
- Variable thread lengths are available for use of threaded holes and through hole fixtures.
- Non removable special bolt (this reduces the risk of non standard bolts).
- Component according to the test criterias of BG/DGUV "GS-OA-15-04".
- Quick and easy installation with just one bolt connection.
- Hand tightening with appropriate wrench is sufficient for a singular lift.
- Please observe torque instructions when lifting point is permanently installed resp. at constant swivelling operations and tilting/ turning actions.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

So-PowerPoint PP-VIP10-3,5t-1"-8UNC with variable length

Artikel-Nr: 8600323



Nominal WLL	3500 kg	7700 lbs
T	94 mm	3-11/16"
A	10 mm	13/32"
D	81 mm	3-3/16"
E	70 mm	2-3/4"
F	25-74 mm	1" to 2-15/16"
M	1"-8UNC mm	1"-8UNC