

Special WBPG-SL M48 for 250t WLL / 730 mm

Artikel-Nr: 7909644




- With 12 pcs RUD-bolts M48
- **Heavy Duty Generation** WBPG up to 250 t WLL.
- **Lifting points pivots 360°. Suspension ring pivots 180°**
- **Detachable suspension ring in the shape of a slingshackle, for the attachment of common lifting means.**
- RUD bolts with special corrosion protection Corrud-DT are included in delivery and are also available as a spare part. Clear marking at the bolt head: RUD, thread size, batch-no., class of strength.
- Component according to the test criterias of BG/DGUV "GS-OA-15-04".

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

Special WBPG-SL M48 for 250t WLL / 730 mm

Artikel-Nr: 7909644



weight	845.00 kg	1862.91 lbs
Nominal WLL	250000 kg	550000 lbs
T	894 mm	35-3/16"
A	730 mm	28-3/4"
B	126 mm	5"
D	300 mm	11-13/16"
E	138 mm	5-7/16"
F	452 mm	17-13/16"
G	380 mm	15"
H	580 mm	22-27/32"
I	74 mm	2-29/32"
K	72 mm	2-27/32"
M	M48 mm	M48
N	120 mm	4-3/4"