

## Eye bolt RS-1 1/8"-7UNC

Artikel-Nr: 57471



- **Considerably higher WLL** (in comparison to DIN 580/582) at vertical load.
- **Large thread and WLL range** (M6-M48, 0.1 t – 8 t).
- **Clear marking of the minimum WLL for all loading directions**
- Quick and easy installation with just one bolt connection.
- In accordance with the test principles of DGUV GS-OA-15-04, eyebolts with rigid eyes serve as mounting aids, e.g. on motors and gear units. There is a trade association clearance certificate available for using the high-strength RUD RS eyebolts.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

## Eye bolt RS-1 1/8"-7UNC

Artikel-Nr: 57471



<b>weight</b>	1.60 kg	3.53 lbs
<b>Nominal WLL</b>	2500 kg	5500 lbs
<b>T</b>	85 mm	3-11/32"
<b>A</b>	45 mm	1-25/32"
<b>B</b>	26 mm	1"
<b>C</b>	24 mm	15/16"
<b>D</b>	60 mm	2-3/8"
<b>E</b>	60 mm	2-3/8"
<b>M</b>	1 1/8"-7UNC mm	1 1/8"-7UNC