

## Eye bolt RS-1 3/4"-5UNC

Artikel-Nr: 58616



- **Considerably higher WLL** (in comparison to DIN 580/582) at vertical load.
- **Large thread and WLL range** (M6-M48, 0.1 t – 8 t).
- **Clear marking of the minimum WLL for all loading directions**
- Quick and easy installation with just one bolt connection.
- In accordance with the test principles of DGUV GS-OA-15-04, eyebolts with rigid eyes serve as mounting aids, e.g. on motors and gear units. There is a trade association clearance certificate available for using the high-strength RUD RS eyebolts.

Other important RUD specific information and specialities to our RUD lifting points can be found in the specific user instruction.

## Eye bolt RS-1 3/4"-5UNC

Artikel-Nr: 58616



<b>weight</b>	6.30 kg	13.89 lbs
<b>Nominal WLL</b>	6000 kg	13200 lbs
<b>T</b>	130 mm	5-1/8"
<b>A</b>	67 mm	2-5/8"
<b>B</b>	43 mm	1-11/16"
<b>C</b>	38 mm	1-1/2"
<b>D</b>	90 mm	3-17/32"
<b>E</b>	100 mm	3-15/16"
<b>M</b>	1 3/4"-5UNC mm	1 3/4"-5UNC