

LIFTING & LASHING POINTS

Selection Guide



WORKING LOAD LIMITS (G - in tonnes)

Single Leg

2, 3 or 4 Leg



Maximum Included Angle (Degrees)

	Description	Single Leg				
		60°	90°	120°		
ACP-TURNADO 	ACP M12	1.35	2.3	1.9	1.35	
	ACP M16	2.5	4.3	3.5	2.5	
	ACP M20	4.0	6.9	5.6	4.0	
	ACP M24	6.3	10.9	8.9	6.3	
	ACP M30	8.0	13.8	11.3	8.0	
VLBG-PLUS 	VLBG-PLUS 0.63t M8	0.63	1.1	0.89	0.63	
	VLBG-PLUS 0.90t M10	0.90	1.6	1.3	0.90	
	VLBG-PLUS 1.35t M12	1.35	2.3	1.9	1.35	
	VLBG-PLUS 2t M16	2.0	3.5	2.8	2.0	
	VLBG-PLUS 3.5t M20	3.5	6.1	4.9	3.5	
	VLBG-PLUS 4.5t M24	4.5	7.8	6.3	4.5	
	VLBG-PLUS 6.7t M30	6.7	11.6	9.4	6.7	
	VLBG-PLUS 8t M36	8.0	13.8	11.3	8.0	
	VLBG-PLUS 10t M42	10.0	17.3	14.1	10.0	
	VLBG-PLUS 15t M42	15.0	26.0	21.1	15.0	
VLBG-PLUS 20t M48	20.0	34.6	28.2	20.0		
VLBS 	VLBS 1.5t	1.5	2.6	2.1	1.5	
	VLBS 2.5t	2.5	4.3	3.5	2.5	
	VLBS 4t	4.0	6.9	5.6	4.0	
	VLBS 6.7t	6.7	11.6	9.4	6.7	
	VLBS 10t	10.0	17.3	14.1	10.0	
	VLBS 16t	16.0	27.7	22.6	16.0	
ABA 	ABA 0.8t	0.8	1.4	1.1	0.8	
	ABA 1.6t	1.6	2.8	2.2	1.6	
	ABA 3.2t	3.2	5.5	4.5	3.2	
	ABA 5t	5.0	8.6	7.0	5.0	
	ABA 10t	10.0	17.3	14.1	10.0	
	ABA 20t	20.0	34.6	28.2	20.0	
	ABA 31.5t	31.5	54.5	44.4	31.5	
VRS-F 	Description	F1	F2	60°	90°	120°
	VRS-F / VRM M6	0.50	0.10	0.17	0.14	0.10
	VRS-F / VRM M8	1.0	0.30	0.52	0.42	0.30
	VRS-F / VRM M10	1.0	0.40	0.69	0.56	0.40
	VRS-F / VRM M12	2.0	0.75	1.3	1.1	0.75
	VRS-F / VRM M16	4.0	1.5	2.6	2.1	1.5
	VRS-F / VRM M20	6.0	2.3	4.0	3.2	2.3
	VRS-F / VRM M24	8.0	3.2	5.5	4.5	3.2
	VRS-F / VRM M30	12.0	4.5	7.8	6.3	4.5
	VRS-F M36	16.0	7.0	12.1	9.9	7.0
	VRS-F M42	24.0	9.0	15.6	12.7	9.0
	VRS-F M48	32.0	12.0	20.8	16.9	12.0

Additional information available from www.rud.com.au